



WATER DETECTION SYSTEM



SERIES 501

NEW

**TO PREVENT
WATER
DAMAGES**



ALARM SWITCH

LED "ALARM INDICATOR"

TERMINAL - DETECTORS

TERMINAL - ALARM (Dry contacts)

3 MODELS AVAILABLE:

DESIGNED FOR:

**RESIDENTIAL,
APARTMENTS,
WAREHOUSES,
CONDOMINIUMS,
OFFICE BUILDINGS.**

PREVENTS FLOODING CAUSED BY:

**SINK,
TOILET,
DISHWASHER,
WATER HEATER,
WASHING MACHINE,
WATER PIPE FAILURE.**

12 Volts DC → model 501-12
120 Volts AC → model 501-120
220 Volts AC → model 501-220

VALVE DIMENSIONS: 3/4 po.

CATEGORY: GLOBE VALVE

BUZZER: Internal

(2) Auxiliary outputs 12 VDC

ELECTRICAL SPECIFICATIONS *

MODEL: 501-120 501-12 501-220

Voltage (input) 120 volts AC 12 Volts DC 220 volts AC

Cycle: 60 Hertz 60 Hertz 50 Hertz

CURRENT:

Standby: 16 mA 41 μ A

Operation: 360 mA 1.8 A

To terminal: 21 μ A 53 μ A

Detectors sensibility: 0-100 kilo-ohms

Detector-connection: In parallel.

Wiring distance: Up to 1000 m.

Recommended wire: AWG #22 (stranded)



UL Listed

* May change without notice.

Manufactured by **GIVE** Systems Inc.
<http://www.aqua-stop.com>

Telephone: (800) 681-7045
Fax: (819) 691-1059